

VT8 light tower

The compact footprint and ease of use are two main features that make the **VT8 light tower** one of the top models in the Generac Mobile® range. High performance balanced with low cost allowed the VT8 to become the best-seller model in the extra-European market.

THE BEST SELLER

The VT8 is **the best seller model** of light tower in the extra-european market, thanks to the vertical mast and the high quality features granted by Generac Mobile®.

Vertical mast

A **telescopic vertical mast** with manual lifting system and a maximum height of 8 meters.

Metal halide lamps

4x1000W powerful metal halide lamps able to illuminate medium and big working areas.

Trailer options

The VT8 is equipped as standard with a **low speed trailer** but it can be also mounted on a **straight road trailer**.

Engine options

You can choose the engine you prefer between between **Yanmar 3TN**, **Kubota D1105** and **Perkins 403-D11**.



Picture shown may not reflect actual configuration.

VT8 P3	Technical Data
Minimum dimensions (L x W x H)	2650 x 1300 x 2460 mm
Maximum dimensions (L x W x H)	2650 x 2460 x 8000 mm
Dry weight	719 kg
Lifting system	Manual
Mast rotation	340°
Lamps power	4 x 1000 W
Lamps type	MH
Total lumen	360000 Lm
Illuminated area	4200 m2
Engine	Perkins 403-D11G
Engine cooling	Liquid
Cylinders (q.ty)	3
Engine speed (50/60 Hz)	1500 / 1800 rpm
Liquid containment (110%)	No
Alternator (kVA/V/Hz)	8/220/50 – 8/240/60
Outlet socket (kVA/V/Hz)	3/220/50 – 3/240/60
Avg. sound pressure	68 dB(A) @ 7m
Wind speed resistance	110 km/h
Tank capacity	75 l
Running time	44 h



Picture shown may not reflect actual configuration.

AFTER-SALES SERVICE:

daniele.crepaldi@generac.com
fabio.busato@generac.com

SPARE PARTS:

manuela.mariani@generac.com

TUTORIALS:

www.towerlight.com/qr/