



INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

Power (kVA)

3 Phase, 50 Hz, PF 0.8

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kW	kVA	kW	kVA	
400/231	26,40	33,00	24,00	30,00	47,63

STANDBY RATING (ESP) Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528. Overload is not allowed.

PRIME RATING (PRP) Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation in accordance with ISO 3046.

General Characteristics

Model Name	DPX-15702
Frequency (Hz)	50
Fuel Type	Diesel
Engine Made and Model	PERKINS 1103A-33G
Alternator Made and Model	PI144G
Control Panel Model	6020
Canopy	AK 20

ENGINE SPECIFICATIONS

Engine	PERKINS
Engine Model	1103A-33G
Number of Cylinder (L)	3 cylinders - in line
Bore (mm.)	105
Stroke (mm.)	127
Displacement (lt.)	3.3
Aspiration	Naturally Aspirated
Compression Ratio	19.25:1
RPM (d/dk)	1500

Oil Capacity (Total With Filter) (lt)	8.3
STANDBY POWER	31/41,55
Prime Power	28.2/37,80
Block Heater QTY	1
Block Heater Power (Watt)	500
Fuel Type	Diesel
Injection Type and System	Direct
Type of Fuel Pump	Delphi Rotary Type
Governor System	Mechanic
Operating Voltage (Vdc)	12 Vdc
Battery and Capacity (Qty/Ah)	1x55
Charge Alternator (A)	65
Cooling Method	Water Cooled
Coolant Capacity (engine only / with radiator) (lt)	/10.2
Air Filter	Dry Type
Fuel Cons. Prime With %100 Load (lt/hr)	7.1
Fuel Cons. Prime With %75 Load (lt/hr)	5.4
Fuel Cons. Prime With %50 Load (lt/hr)	3.9

ALTERNATOR CHARACTERISTICS


Manufacturer	Stamford
Alternator Made and Model	PI144G
Frequency (Hz)	50
Power (kVA)	30
VOLTAGE (V)	400
Phase	3
A.V.R.	AS480
Voltage Regulation	(+/-)1%
Insulation System	H
Rated Power Factor	0.8
WEIGHT WOUND ROTOR (Kg)	57.39
COOLING AIR (m ³ /min)	6

Open Gen.Set Dimensions (mm)

LENGHT	1500
WIDTH	900
HEIGHT	1210
DRY WEIGHT (kg.)	665
TANK CAPACITY (lt.)	70

Gen.Set Canopy Dimensions

LENGHT	1500
WIDTH	900
HEIGHT	1210
DRY WEIGHT (kg.)	665
TANK CAPACITY (lt.)	70




INTRODUCTION

Sound-attenuated and Weather-protective Enclosures Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

Control Panel

Control Module	DSE
Control Module Model	6020
Communication Ports	MODBUS



Devices

-DSE, model 6020 Auto Mains Failure control module.

-Battery charger input 198-264 volt, output 27,6 V 5 A (24 V) or 13,8 Volt 5A (12V)