

# **Engine Model: KTA50-G3 - Driven by Cummins Engine**



	Genset Model	Prime Rating	Standby Rating	
50 Hz	DPX-18818	1000 kW 1250 kVA	1100 kW 1375 kVA	
60 Hz	DPX-18818	1100 kW 1375 kVA	1260 kW 1575 kVA	

- Authorized Genset Original Equipment Manufacturer (GOEM) of Cummins Inc.
- Fully load tested and checked under standard procedures
- Tailor fit specific operational needs (please turn over)

# **Specifications**

Engine	50 Hz	60Hz	
Engine Model - Cummins	KTA50-G3		
Engine Speed	1500rpm	1800rpm	
Fuel consumption (Standby) Liter/hour 100%	293	330	
Fuel consumption (Prime) Liter/hour			
100%	261	291	
75%	199	222	
50%	139	157	
25%	76	89	

Engine Type	4-Cycle, 16 Cylinder	
Aspiration	Turbocharged & aftercooled	
Bore x Stroke	159mm x 159mm	
Displacement	50.3 Liter	
Compression Ratio	13.9:1	
Lubrication System - Total System Capacity	177 Liter	
Cranking Motor	24 Volt	
Fuel injection System	Direct Injection Cummins PT	

## **Control System**

## Standard Control Panel System

- Deep Sea Electronics: key start, auto start, synchronizing
- ComAp Control: single gen-set controllers, paralleling gen-set controllers
- Analog Instrument Panel





Alternator	
Alternator Model - STAMFORD Alternators	PI734B
Rated Power Factor	0.8
Insulation System	Class H
Winding Pitch	Two Thirds
Winding Leads	6
Protection	IP23


Control System - Separately Excited By P.M.G.


A.V.R.	MX341	MX321	
Voltage Regulation	± 1 %	± 0.5 %	With 4% Engine Governing

#### **Dimensions and Weights**









A:	Length	(mm	)

C: Height(mm)

Gross Weight (kgs)

Open-set	5112	2120	2431	9570	
Enclosure-set	6058	2438	2590	16600	

<sup>\*</sup> Dimensions and weights are for guidance only. Do not use for installation design.

### **Available Options**

We offer a wide range of optional equipment to tailor your generating sets so as to meet your operational needs. Options include:

B: Width(mm)

- Alternator heater, engine heater or panel heater
- Circuit breaker 3P/4P
- •
- Customization of the fuel tank size
- Silencer
- Tailor-made enclosure sets

For further information on the standard or optional equipment accompanying this product, please feel free to contact us.

#### **Documentation**

A full set of operation and maintenance manuals as well as circuit wiring diagrams.

#### Warranty

Parts warranty up to 1500 hours or a year of operation whichever comes first. Please contact us for full details on warranty cover.

\*All specifications are subject to change without notice.