

# Product Specifications for 1103A-33TG

## Total Power Range

Gross Mechanical Output	42 - 70 kWm
Typical Electrical Output	45-75 kVA (36-60 kWe)
Rated Speed	1500/1800 rpm

## 50 Hz Typical Electrical Output

Prime	45 - 60 kVA
Standby	50 - 66 kVA

## 60 Hz Typical Electrical Output

Prime	43 - 55 kWe
Standby	47- 60 kWe

## Emission Standards

Emissions	Fuel Optimised
-----------	----------------

## General

Number of Cylinders	3 vertical inline
Bore	105 mm
Stroke	127 mm
Displacement	3.3 l
Compression Ratio	17.3:1
Aspiration	Turbocharged

<b>Combustion System</b>	Direct injection
<b>Rotation from Flywheel End</b>	Anti-clockwise
<b>Cooling System</b>	Liquid
<b>Aftertreatment</b>	-
<b>Typical Alternator Efficiency</b>	89%
<b>Switchable</b>	Yes

## ElectropaK Dimensions

<b>Length</b>	1150 mm
<b>Width</b>	760 mm
<b>Height</b>	1300 mm
<b>Dry Weight</b>	420 kg

## Disclaimer

<b>Note 1</b>	*Final dimensions dependent on selected options
---------------	---

## Definitions

<b>Prime Power</b>	Unlimited hours usage with an average load factor of 80% of the published prime power over each 24 hour period. A 10% overload is available for 1 hour in every 12 hours of operation.
--------------------	--

<b>Standby Power</b>	Limited to 500 hours annual usage, up to 300 hours of which may be continuous running. No overload is permitted.
----------------------	--

## 1103A-33TG Standard Equipment

### Air inlet system

Mounted air filter

### Control system

12 volt starter motor and 12 volt 65 amp alternator with DC output  
12 volt shutdown solenoid energised to run

## Cooling system

Mounted radiator and piping

Thermostatically controlled system with gear driven circulation pump and belt driven pusher fan

## Flywheels and flywheel housing

High inertia flywheel to SAE J620 size 10/11½

SAE 3 flywheel housing

## Fuel system

Next generation fuel filter

Rotary type pump

## General

Front engine mounting brackets

## Oil system

Wet sump with filler and dipstick

Spin-on oil filter