



Technical Data

Model		275kva
Prime power	kva	250
	kw	200
Standby power	kva	275
	kw	220
Rated voltage line to line	V	400
Rated current	A	360,9
Maximun sound level	dB@7m	75

Engine-YTO

Model		YM6S4L-D
Aspiration	Four-stroke, water-cooled, in-line, direct injection, turbocharged	
No. cylinders		6
Displacement	L	9,726
Bore*Stroke	mm	126x130
Compression ratio		17.5:1
Rated speed	r/min	1500
Governor		Electrcial system
Engine wet weight	kg	1000±20
Engine dimension	mm	1805×950×2200
Fire order		1-5-3-6-2-4
Start Motor	V	24

Exhause System

Max exhaust back pressure	kPa	10
---------------------------	-----	----

Air intake System

Max inlet pressure (Dirty air)	kPa	6,3
Max inlet pressure (Clean air)	kPa	3,7

Fuel System

110% load(Standby power)	L/h	64,9
100% load(Prime power)	L/h	54
75% load(Prime power)	L/h	40,5
50% load(Prime power)	L/h	27
25% load(Prime power)	L/h	15,8
Fuel capacity for silent genset	L	285

Lubrication System

Idle speed oil pressure	kPa	≥98
Governed speed oil pressure	kPa	294~490
Max Oil temp	°C	115
Oil capacity	L	24

Cooling System

Coolant capacity--Engine only	L	23
Maximum top tank temperature	°C	99
Thermostat operating range.	°C	.71~82
Coolant intake pipe size	mm	52
Coolant outlet pipe size	mm	52

Standard Features

Engine(YTO Engine)	●
Radiator 50°C max,fans are driven by belt	●
12/24V charge alternator	●
Alternator: single bearing alternator IP23	●
insulation class H/H	●
Standard auto control system	●
One set of air filter, fuel filter, oil filter	●
Main line circuit breaker / ACB	●
Base fuel tank	●
One 12V/Two 24V batteries, rac and cable	●
Exhaust system(Ripple flex exhaust pipe)	●
Exhaust siphon, flange, muffler	●
User manual	●
Battery charge	●

Options

Water heater	○
Alternator heater	○
PMG	○
Water oil separator	○
Daily fuel tank	○
Remote control panel	○
Automatic transfer switch/ATS	○
Switch box	○

Standard: ● Options: ○

Alternator

Model	CJ274K
-------	--------

Phase		3
Voltage	V	230/400
Wiring Type		12 wires
Bearing		1
Power factor		0,8
Frequency	Hz	50
Prime power	KVA	250
Exciter Type		Brushless, self-excitation
Voltage regulation	%	±0.5
Protection Grade		IP 23
Insulation grade		H

Controller-Deepsea

Model DSE 6120

7 configurable digital inputs

Built-in governor and AVR control

Base load (kW export) functionality

Mains (utility) de-coupling protection

Generator power (kW, kVA) monitoring


Overload (kW & kV Ar) protection

Emergency stop

Start failure



Unit Dimensions(Basic unit)

		
Silent Type		
L*W*H	mm	3800*1300*1970
Weight	kg	2750

Warranty

YTO Engine

12 months from date of purchase or 1000 hours.

Generator

12 months from date of purchase or 1000 hours
(whichever comes first).