

MAIN FEATURES

Silenced, weather proof canopy, made of steel with AL Zn anticorrosion coating	Welded frame with integrated fuel tank and drip tray, protecting environment from leakage of the fluid.
Limited number of screws outside the canopy.	Wide range of fuel tank capacities available.
Electrical box protected by genset canopy, with controller display.	Possibility of increased protection against fuel leakage – fuel tank separated from the frame.
Cable entry protected by rubber cover.	Key locked fuel inlet outside of the canopy.
Power socket available outside of the canopy.	Anchoring points covered by external covers.
Easy maintenance access to major components.	Crane or pallet truck lifting.
High quality noise insulation materials.	High quality mufflers for exhaust system.



GENERAL DATA

Model	DPX-17654	Nominal power P.R.P.:
Standby power E.S.P. [kVA] / [kW]	63,0 / 50,0	Prime power available in variable load application in accordance with ISO 8528, 10% overload capacity is available for a period of 1 hour within a 12-hour period of operation. Average power consumption should not exceed 80% P.R.P for each 24h of work.
Prime power P.R.P. [kVA] / [kW]	60,0 / 48,0	Stand-by power E.S.P.:
Prime current P.R.P [A]	86,0	Emergency standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload allowed, limited to 500 operation hours per year. Limited to 300 operation hours of continuous duty.
Frequency [Hz]	50	Remark:
Voltage [V]	400	Ratings represent the genset performance capabilities to standard conditions specified in ISO 8528-1
Exhaust emission	non-emission	Norms and directives:
Fuel type	Diesel (EN 590)	<input type="checkbox"/> Machinery directive 2006/42/WE
Fuel consumption - 50% load [l/h]	7,2	<input type="checkbox"/> Low voltage directive 2006/95/WE
- 75% load [l/h]	10,4	<input type="checkbox"/> EC directive 2004/108/WE
- 100% load [l/h]	13,9	<input type="checkbox"/> Noise directive 2000/14/WE
- 110% load [l/h]	15,4	<input type="checkbox"/> Emission directive 97/68/WE
Standard fuel tank capacity [l]	120	<input type="checkbox"/> ISO 8528-1/2005, PN-ISO 8528-5/2005
Autonomy with 100% load [h]	8,6	<input type="checkbox"/> PN-EN 12601
Engine control voltage [V]	12	<input type="checkbox"/> PN-EN 60204-1
Weight without fuel [kg]	1140	
Dimensions L x W x H [mm]	2353 x 1088 x 1466	
Guaranteed noise power Lwa [dBA]	95	
Acoustic pressure Lpa (dla 7m) [dBA]	63,9 ± 2,2	

STANDARD CONTROLLER

Controller type: AMF 25
Easy to operate, intuitive graphical interface
Real time clock with battery supply
AMF function available
Flexible event based history with up to 119 events
3 Phase generator current measurement
Generator and Mains phase voltage measurement
Active/reactive power measurement
Active and reactive energy counter
Running hours counter
Battery charging alternator circuit connection
Fuel level measurement
Generator protection (over/under frequency, voltage, overcurrent)
Communication with ECU supporting CAN J1939 standard
Communication interface RS 485 and RS 232 supporting Modbus RTU (IL-NT RS232-485 module required)
GSM modem / wireless internet (IL-NT GPRS module required)
Internet/Ethernet communication (IB-Lite module required)
InteliMonitor software for single gen-set view
WebSupervisor software for Android mobile devices or PC's for fleet management
Active SMS or e-mail (IL-NT GPRS or IB-Lite module required)



ENGINE

ALTERNATOR

Brand	Perkins	Brand	Leroy Somer
Type	1103A-33TG2	Type	TAL042 H
Made in	Great Britain	Made in	France
Engine power [kW]	53,8	Power (40 °C, 1000m a.m.s.l.) [kVA]	60,0
Emission standard*	non-emission	Stand by power (27 °C, 1000m a.m.s.l) [kVA]	63,0
Rotation per minute [rpm]	1500	Efficiency [%]	88,8
Engine governor	mechanical	Voltage regulator type	AVR SX460
Governor class**	G2	Voltage accuracy [%]	+/- 1
Displacement [l]	3,3	IP protection	IP 23
No of cylinder	3	Insulation class	H
Fuel system	direct injection	Total harmonic content THD [%]	<1,5
Electrical system [V]	12	Reactance Xd'' [%]	12
Coolant	Shell Anti Freeze		
Cooling system capacity [l]	10,2		
Engine oil	Shell Rimula R4L		
Oil pan capacity [l]	7,9		
Fuel type	Diesel (EN 590)		
Fuel consumption at 75% load [l/h]	10,4		
Fuel consumption at 100% load [l/h]	13,9		

* According directive 97/68/WE non road mobile machinery engine emission.

** According PN-ISO 8528-5/2005

STANDARD EQUIPMENT

OPTIONAL EQUIPMENT

Controller ComAp AMF25	Three phase sensing AVR
Controller switch	Alternator with PMG
3 Pole GCB Eaton LZMC2-VE160	4 Pole GCB Schneider NSX Micrologic 2.3
Shunt GCB release coil	Oil draining hand pump
Analog AVR	Fuel and retention pump
Acoustic alarm	Electronic engine speed governor
Emergency stop button	Oil pressure sensor
Starting batteries 100 Ah	Engine temperature sensor
Battery charger	Drip space level sensor
Engine preheating with thermostat	Dedicated (non-standard) fuel tank *
Engine oil Shell Rimula R4L	External fuel tank 1 000 – 10 000 l
Oil low pressure switch	Fuel tank filling pump and shut-off valve
Engine high temperature switch	Battery disconnection switch
Fuel tank integrated in frame with drip tray	Socket for full power output
Fuel inlet outside of the canopy with lock	Power output – power lock type
Fuel level measurement	Power socket box with appropriate protections *
Fuel filter with water separator	Transfer switch controlled by generator controller
Exhaust compensator and silencer	ATS with ATS controller
Coolant Shell Anti Freeze	GPRS communication card
Coolant inlet outside of the canopy	Ethernet card
Engine and alternator vibro isolators	RS 485, RS 232 card
Silenced canopy made with Al-Zn	Remote display
Standard color RAL 7032	Nonstandard canopy color
Transportation brackets	

*according to individual agreement

INSTALLATION GUIDELINES

Power terminal	GCB terminal
Recommended cable for up to 30m power cable way	Flexible 5x25mm ²
Recommended cable for do 30m generator heater supply	Flexible 3x2,5mm ²
*For additional cable connection with ATS see ATS wiring diagram	
Exhaust pipe min diameter (max. 7 m, 4 bends)	60,3 mm
Exhaust pipe min diameter (max. 15 m, 4 bends)	76,1 mm

MAINTENANCE GUIDELINES

Fuel filters replacement	500 h / 1 year
Oil replacement	After first 100h, then every 500 h / 1 year
Oil filters replacement	After first 100h, then every 500 h / 1 year
Coolant replacement	1000 h / 2 years
Battery replacement	2 years
Electrical installation supervising	According to local requirements, at least once per year

WARRANTY

Back-up power generators	60 months up to 1000 working hours, under condition of required maintenance according to the warranty conditions
Continuous work generators	12 months up to 1000 working hours